

**!!! NOT: TABLODAKİ EŞYAYA İLİŞKİN VERGİ İNDİRİMİ TALEPLERİ GTİP BAZINDA DEĞİL KARŞILARINDA YER ALAN ÖZEL TANIMLAR İÇİN YAPILMIŞTIR. İTİRAZ VEYA DESTEK TALEPLERİNİN BU ÖZEL TANIMLAR DİKKATE ALINARAK YAPILMASI GEREKMEKTEDİR!!!**

**Ocak 2018'den Sonra Gümrük Vergisi İndirimi Talep Edilen Eşya**

CN code	TARIC	Reference Mail	Description
2814 10 00		1500375/2017	Anhydrous ammonia (CAS RN 7664-41-7)
2814 10 00		1500078/2017	Anhydrous ammonia (CAS RN 7664-41-7)
2833 29 80		1589379/2017	Cesium sulfate (CAS RN 10294-54-9)
2841 80 00		1589327/2017	Ammoniummetawolframate (Ammoniummetatungstate), (CAS RN 12028-48-7) min 88 % WO <sub>3</sub>
2924 29 98		1500416/2017	2'-methoxyacetoacetanilide (CAS RN 92-15-9)
2933 29 90		1518846/2017	4-(3-(4-Cyano-3-(trifluoromethyl)phenyl)-5,5-dimethyl-4-oxo-2-thioxoimidazolidin-1-yl)-2-fluoro-N-methylbenzamide
2933 59 95		1518895/2017	1-[3(R)-[4-Amino-3-(4-phenoxyphenyl)-1H-pyrazolo[3,4-d]pyrimidin-1-yl]piperidin-1-yl]-2-propen-1-one
2934 99 90		1518802/2017	(1S)-1,5-anhydro-1-[3-[[5-(4-fluorophenyl)-2-thienyl]methyl-4-methylphenyl]-D-glucitol hemihydrate (CAS RN 928672-86-0)
3105 30 00		1489155/2017	Diammonium hydrogen orthophosphate (CAS RN 7783-28-0) [for use in the manufacture of complete fertilizer] (1)
3105 30 00		1500692/2017	Diammonium hydrogenorthophosphate (diammonium phosphate) (CAS RN 7783-28-0)
3206 11 00		1586014/2017	Titanium dioxide (CAS RN 13463-67-7) - of a purity by weight of 94,7 % or more, but not more than 95,3 %, and - with an average grain-size of 0,26 µm or more but not more than 1,3 µm for use in the manufacture of printing inks (1)
3824 99 92		1500743/2017	Mixture of alkyldimethyl tertiary amines containing by weight: - 60 % or more but not more than 80 % of N,N-dimethyldodecylamine (CAS RN 112-18-5) - 20 % or more but not more than 30 % of N,N-dimethyltetradecylamine (CAS RN 112-75-4) - [Not more than 5 % of N,N-dimethyldecylamine (CAS RN 1120-24-7) - Not more than 5 % of N,N-dimethylhexadecylamine (CAS RN 112-69-6) - Not more than 0,3 % of N,N-dimethyloctylamine (CAS RN 7378-99-6)]
5504 90 00		1528203/2017	Bamboo Staple fiber
ex 7410 21 00	55	1518757/2017	Plates: - consisting of at least one layer of fibreglass fabric impregnated with epoxide resin, - covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, - with a dielectric constant (DK) of less than 5,4 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, - with a loss tangent of less than 0,035 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, - with a comparative tracking index (CTI) of 600 or more
7603 10 00		1503685/2017	Aluminium powder in the form of microspheres of a diameter of 4 µm or more but not more than 11 µm, with a purity by weight of 99,8 % or more
7603 10 00		1503568/2017	Aluminium powder in the form of microsphere of a diameter of 7 µm or more but not more than 240 µm, with a purity by weight of 99,99 % or more
7609 00 00		1443028/2017	Attachment parts of an aluminium alloy containing manganese, with a material weakening of not more than 30 %
8481 80 85		1443074/2017	Exhaust valve for use in the manufacture of motorcycle exhaust gas systems (1)
9027 10 90		1445452/2017	Lambda sensor with a length of not more than 60 mm
2712 20 90		5503506/2016	Paraffin wax containing by weight less than 0,75 % of oil
2903 22 00		295295/2011	Trichloroethylene (CAS RN 79-01-6)
2905 31 00		296972/2011 5555215/2016	Ethylene glycol (ethanediol) (CAS RN 107-21-1)
2932 12 00		5457221/2016	2-Furaldehyde (furfuraldehyde)
ex 3204 17 00	49	1349348/2016	Colourant C.I. Pigment Red 2 (CAS RN 6041-94-7) and preparations based thereon with a Colourant C.I. Pigment Red 2 content of 80 % or more by weight
ex 3824 99 92	71	5573365/2016	Mixtures containing by weight: - 60 % or more but not more than 90 % of 2-chloropropene (CAS RN 557-98-2), - 8 % or more but not more than 14 % of (Z)-1-chloropropene (CAS RN 16136-84-8),

			<ul style="list-style-type: none"> <li>- 5 % or more but not more than 23 % of 2-chloropropane (CAS RN 75-29-6),</li> <li>- not more than 6 % of 3-chloropropane (CAS RN 107-05-1), and</li> <li>- not more than 1 % of ethyl chloride (CAS RN 75-00-3)</li> </ul>
5504 10 00		1367832/2016	Artificial staple fibres of viscose rayon not carded, combed or otherwise processed for spinning
ex 5505 10 10	10	5451208/2016	Waste of synthetic fibres (including noils, yarn waste, and garnetted stock) of nylon or other polyamides (PA6 and PA66)
ex 7019 40 00 ex 7019 52 00	60 20	1290020/2016	<p>15-3 DE: Request for amendment</p> <p>E-fibre glass fabrics:</p> <ul style="list-style-type: none"> <li>- having a weight of 20 g/m<sup>2</sup> or more, but not more than 214 g/m<sup>2</sup>,</li> <li>- impregnated with silane,</li> <li>- having a humidity content by weight of 0,13 % or less, and</li> <li>- having not more than 3 hollow fibres out of 100 000 fibres,</li> </ul> <p>not for use in the composite industry and for industrial applications, but for the exclusive use in the manufacture of prepreg plates, rolls or laminates, which are further processed by PCB producers to the printed circuit boards (PCB)</p> <p>E-fibre glass fabrics:</p> <ul style="list-style-type: none"> <li>- having a weight of 20 gr/m<sup>2</sup> or more, but not more than 209 g/m<sup>2</sup>,</li> <li>- impregnated with silane,</li> <li>- having a humidity content by weight of 0,13 % or less, and</li> <li>- having not more than 3 hollow fibres out of 100 000 fibres,</li> </ul> <p>for use in the manufacture of prepreg plates, rolls or laminates for the production of printed circuit boards for the motor vehicle industry (1)</p>
7601 20 80		5555261/2016	<p>22.3.17 TR proposal:</p> <p>Aluminium ingot including by weight;</p> <ul style="list-style-type: none"> <li>- 6,5 % or more but not more than 12 % of silisium,</li> <li>- 0,010 % or more but not more than 0,055 % of stronsium,</li> <li>- 0,08 % or more but not more than 0,20 % of titanium,</li> <li>- 0,02 % or more but not more than 0,33 % of magnezium</li> </ul> <p>Unwrought aluminium, aluminium alloys – other</p>
ex 8414 90 00	70	5572918/2016	<p>Aluminium alloy compressor wheel with:</p> <ul style="list-style-type: none"> <li>- a diameter of 20 mm or more, but not more than 130 mm, and</li> <li>- a weight of 5 g or more, but not more than 800 g</li> </ul> <p>for use in the manufacture of combustion engines (1)</p>
ex 8714 10 90	60	5501376/2016	Pistons for suspension systems, having a diameter of not more than 55 mm, of sintered steel
<b>CN code</b>	<b>TARIC</b>	<b>Reference Mail</b>	<b>Description</b>
2811 29 90		1500331/2017	Tellurium Dioxide (CAS NR 7446-07-3)
2841 50 00		1503285/2017	Potassium dichromate (CAS RN 7778-50-9)
2841 90 30		1563923/2017	Potassium metavanadate
2841 90 85		1564962/2017	Lithium Nickel Cobalt Aluminum Oxide powder with: <ul style="list-style-type: none"> <li>- a particle size of less than 10 µm,</li> <li>- a purity by weight of more than 98 %</li> </ul>
2850 00 20		1527535/2017	TRISILANE / Si <sub>3</sub> H <sub>8</sub>
2850 00 20		1514483/2017	Disilane (Si <sub>2</sub> H <sub>6</sub> ) (CAS RN 001590-87-0)
2903 39 19		1503351/2017	5-Bromopent-1-ene (CAS RN 1119-51-3)
2903 39 28		1514474/2017	PFC-116 Hexafluoroethane (R116) Non-Flammable and non toxic gases
2903 39 29		1514499/2017	Octafluoropropane (RC218) (CAS RN 76-19-7)
2903 39 39		1525373/2017	1,1,2,3,4,4-HEXAFLUORO-1,3-BUTADIENE
2903 89 80		1514559/2017	Octafluorocyclobutane (RC318) PFC-c-318; perfluorocyclobutane (CAS RN 115-25-3)
2912 29 00		1564222/2017	Cinnamaldehyde (CAS RN 104-55-2)
2918 99 90		1652360/2017	Naproxen Sodium
2918 99 90		1489058/2017	Ethyl 3-ethoxypropionate (CAS RN 763-69-9)
2919 90 00		1296542/2017	Phosphorous acid,3,3',5,5'-tetrakis(1,1,-dimethylethyl)-6,6'-dimethyl(1,1'-biphenyl)-2,2'-diyl tetra-1-naphthalenyl ester (CAS RN 198979-98-5)
2921 45 00		1564197/2017	8-Aminonaphthalene-2-sulphonic acid (CAS RN 119-28-8)
2921 45 00		1564151/2017	1-Naphthylamine (CAS RN 134-32-7)
2922 49 85		1445698/2017	L-alanine isopropyl ester HCl (CAS RN 62062-65-1)
2922 50 00		1489079/2017	3,5-Diiodothronine (CAS RN 1041-01-6)
2924 19 00		1489107/2017	Isobutylidenediurea (CAS RN 6104-30-9)
2931 90 00		1562984/2017	Ferrocene for use in additives designed for home heating fuels
2932 20 90		1565410/2017	L-Lactide (CAS RN 4511-42-6) or D-Lactide (CAS RN 13076-17-0) or dilactide (CAS RN 95-96-5)
2933 39 99		1500584/2017	1-[2-[5-Methyl-3-(trifluoromethyl)-1H-pyrazol-1-yl]acetyl]piperidine-4-

			carbothioamide (CAS RN 1003319-95-6)
2933 39 99		1442986/2017	Pyridine-2,6-dicarboxylic acid (CAS RN 499-83-2)
2933 99 80		1497677/2017	(S)-indoline-2-carboxylic acid (CAS RN 79815-20-6)
2933 99 80		1489124/2017	Epoxiconazole (ISO) (CAS RN 133855-98-8)
2933 99 80		1497747/2017	5-(4-Bromomethyl-1,1-biphenyl-2-yl)-1-triphenylmethyl-1H-tetrazole
2934 20 80		1565183/2017	Benthiavalicarb-isopropyl (ISO) (CAS RN 177406-68-7)
2934 99 90		1565216/2017	2-benzyl-2-dimethylamino-4-morpholinobutyrophenon (CAS RN 119313-12-1)
2934 99 90		1500627/2017	1-[5-(2,6-Difluorophenyl)-4,5-dihydro-1,2-oxazol-3-yl]ethanone (CAS RN 1173693-36-1)
2934 99 90		1309539/2017	(6R,7R)-7-Amino-8-oxo-3-(1-propenyl)-5-thia-1 azabicyclo [4.2.0]oct -2 -ene-2carboxylic acid (7-APRA) (CAS RN 120709-09-3)
2938 90 90		1522623/2017	Purified Steviol Glycoside consisting of 80 % or more but not more than 90 % Rebaudioside M
2938 90 90		1522664/2017	Purified steviol glycoside, rebaudioside A
3105 30 00		1523088/2017	Diammonium hydrogenorthophosphate (diammonium phosphate) (CAS RN 7783-28-0)
3105 30 00		1381354/2017	Diammonium hydrogenorthophosphate (CAS RN 7783-28-0)
3204 15 00		1528424/2017	VAT DYES C.I. vat blue 1 dyes item (CAS RN 482-89-3) and construction equals or more 94 % C.I. vat blue covering preparations
3204 17 00		1489188/2017	Colourant C.I. Pigment Orange 13 (CAS RN 3520-72-7) and preparations based thereon with a colourant C.I. Pigment Orange 13 content of 80 % or more by weight
3204 17 00		1515121/2017	Colourant C.I. Pigment Black 12 (CAS RN 68187-02-0) and preparations based thereon with a colourant C.I. Pigment Black 12 content of 50 % or more by weight
3204 17 00		1515151/2017	Colourant C.I. Pigment Brown 24 (CAS RN 68186-90-3) and preparations based thereon with a colourant C.I. Pigment Brown 24 content of 50 % or more by weight
3204 17 00		1515181/2017	Colourant C.I. Pigment Yellow 160:1 (CAS RN 35773-43-4 ) and preparations based thereon with a colourant C.I. Pigment Yellow 160:1 content of 50 % or more by weight
3204 19 00		1489199/2017	Colourant C.I. Solvent Yellow 133 (CAS RN 51202-86-9) and preparations based thereon with a colourant C.I. Solvent Yellow 133 content of 97 % or more by weight
3204 19 00		1523974/2017	Colourant C.I. Solvent Red 175 (CAS RN 68411-75-6) and preparations based thereon with a Colourant C.I. Solvent Red 175 content of 40 % or more by weight
3208 90 19		1489278/2017	Lösung eines Polymers in Cyclopentanon (CAS RN 120-92-3)
3403 99 00		1515223/2017	Polypropylene Glycol Monobutyl Ether of an alkalinity of not more than 1ppm of sodium (CAS RN 9003-13-8)
3504 00 90		1565336/2017	Extensive casein protein hydrolysate
3506 91 90		1489313/2017	Klebstoff auf der Grundlage eines Polymeren gelöst in D-Limonen (CAS RN 5989-27-5)
3603 00 90		1563699/2017	Igniters for gas generators
3801 10 00		1570492/2017	Natural graphite based powder with: - an average particle size of 10.8 µm or more but not more than 13.0 µm - an iron content of less than 40 ppm - a copper content of less than 5 ppm - a nickel content of less than 5 ppm - an average surface area (N2 atmosphere) of 3.0 m2/g or more but not more than 4.36 m2/g - a magnetic metal impurity of less than 0.3 ppm
3815 90 90		1443007/2017	Powder catalyst - consisting by weight of 95 (± 1) % titanium dioxide and 5 (± 1) %silicon dioxide - [having a specific surface area of 120 (±10) m2/g and - containing not more than 10 % particles with a size of more than 212 µm]
3824 99 92		1562945/2017	Preparation containing: - 60 % or more but not more than 75 % of Solvent naphtha (petroleum), heavy arom. (CAS RN 64742-94-5) - 15 % or more but not more than 25 % of 4-(4-nitrophenylazo)-2,6-di-sec-butyl-phenol (CAS RN 111850-24-9), and - 10 % or more but not more than 15 % of 2-sec-Butylphenol (CAS RN 89-72-5)
3907 20 99		1652578/2017	Surfanol Isoamyl Alcohol Polyoxyethylene Ether
3921 19 00		1515277/2017	Rolls of Expanded Polytetrafluoroethylene [ePTFE] of a width of 1,600 mm or more but not more than 1,730 mm [used in the manufacture of a bi-component ePTFE]
3921 19 00		1575341/2017	Multilayer separator foil: - containing one polyethylene layer between two polypropylene layers and whether or not containing a safety coating of aluminium-oxide, - with a width of 65 mm or more but not more than 170 mm, - with a total thickness of 0.01 mm or more but not more than 0.03 mm
3921 19 00		1489232/2017	Microporous monolayer polypropylene film or film of three microporous layers

			(polypropylene / polyethylene / polypropylene), in each case - with Zero TD shrinkage, - with a total thickness from 10 to 50 µm, - with a membrane width from 15 mm to 800 mm, - in the form of rolls from 200 to 3000 m, - with an average pore size between 0.02 and 0.1 µm, of a kind used for the manufacture of lithium ion or zinc air batteries.
7019 11 00		1563023/2017	Chopped strands measuring 800 tex or more but not more than 2000 tex, composed of continuous glass filaments of 10µm (±1 µm)
7019 12 00		1503394/2017	S-glass stratifils (rovings): - composed of continuous glass filaments of 9 µm (± 0,5 µm) - measuring 200 tex or more but not more than 680 tex
7020 00 10		1489261/2017	Rohmaterial [für optische Elemente] aus geschmolzenem Siliciumdioxid in regelmäßigen Formen (z.B. Blöcke, Rundscheiben, Segmente) und verschiedenen Abmessungen
7202 21 00		1653227/2017	Ferrosilicon (including silicon more than %55 but less than %80)
7202 30 00		1653260/2017	Ferrosilicomanganese
7315 11 90		1379018/2017	Roller type steel timing chain with a fatigue limit of 2 kN at 7 000 rpm or more for use in the manufacture of engines of motor vehicles (1)
8108 20 00		1516795/2017	Titanium alloy slab, with - a height of 20,32 cm or more, - a length of not more than 289,6 cm, - a width of 40,64 cm or more, - a weight of not more than 965 kg containing alloy elements by weight of: - 5.2 % or more but not more than 6.2 % of aluminium - 2.5 % or more but not more than 4.8 % of vanadium
8108 90 30		1518694/2017	Titanium alloy wires or rods, with: - a uniform solid cross-section along their whole length in the shape of circle with a diameter of 0,8 mm or more, but not more than 5.0 mm, - a titanium content by weight of 0,3 % or more, but not more than 0,7 %, - an aluminium content by weight of 0,3 % or more, but not more than 0,6 %, - a silicone content by weight of 0,1 or more, but not more than 0,3 % , - a niobium content by weight of not more than 0.2 % , - iron - not more than 0,15 % by weight of other chemical elements
8108 90 50		1565292/2017	Cold or hot rolled plates, sheets, and strips with - a thickness of 0,4 mm or more, but not more than 100,0 mm, - a length of not more than 14000 mm, and - a width of not more than 4000 mm; each in the grades Gr.1, Gr.2, Gr.3, Gr.4, Gr.5, Gr.7, Gr.9, Gr.11, Gr12 or Gr.23 (according to ASTM B861)
8108 90 60		1565251/2017	Seamless pipes, tubes and U-bends with: - a diameter of 19,0 mm or more but not more than 159,0 mm, - a wall thickness of 0,4 mm or more but not more than 8,0 mm, and - a maximum length of 18 meter, in the grades Gr.1, Gr.2, Gr.3, Gr.4, Gr.5, Gr.7, Gr.9, Gr.11, Gr12 or Gr.23 (according to ASTM B861)
8108 96 00		1443058/2017	Tungsten wire - containing by weight 99,95 % or more of tungsten and - with a maximum cross-sectional dimension of not more than 1,02 mm
8409 99 00		1378876/2017	High pressure oil jet for engine piston cooling and lubrication with: - an opening pressure of 1 bar or more, but not more than 3 bars, - a closing pressure of more than 0,7 bar, - a one-way valve for use in the manufacture of engines of motor vehicles (1)
8409 99 00		1378927/2017	Metal alloy intake and exhaust valve with a Rockwell hardness HRC 20 or more, but not more than HRC 50 for use in the manufacture of engines of motor vehicles (1)
8409 99 00		1379092/2017	Intake manifold composed of steel and plastic part for air supply to the engine cylinders comprising at least: - throttle, - boost pressure sensor for use in the manufacture of engines of motor vehicles (1)
8414 80 80		1564107/2017	Air membrane compressor with: - a flow of 4,5 l/min or more, but not more than 7 l/min; - power input of not more than 8,1 W; - a gauge pressure capacity not exceeding 400 hPa (0,4 bar) of a kind used in the pneumatic comfort system of motor vehicle seats

8483 40 90		1443106/2017	Hydrostatic transmission with <ul style="list-style-type: none"> <li>- measurements (without shafts) of not more than 154 mm x 115 mm x 108 mm</li> <li>- a weight of not more than 3,3 kg</li> <li>- a maximum rotation speed of the input shaft of 2700 rpm or more, but not more than 3200 rpm</li> <li>- a torque of the output shaft of not more than 10,4 Nm</li> <li>- a rotation speed of the output shaft of not more than 930 rpm at 2800 rpm input speed</li> <li>- an operating temperature range of -5 °C or more, but not more than +40 °C</li> </ul> for use in the manufacture of hand-operated lawn mowers of heading 8433 11 90 (1)
8483 40 90		1443085/2017	Hydrostatic transmission with <ul style="list-style-type: none"> <li>- a reduction of 20,63:1 or more, but not more than 22,68:1</li> <li>- an input speed of not less than 1800 rpm when loaded and of more than 3 000 rpm when not loaded</li> <li>- a continuous output torque of 142 Nm or more, but not more than 156 Nm</li> <li>- an intermittent output torque of 264 Nm or more, but not more than 291 Nm</li> <li>- an axle shaft diameter of 19,02 mm or more, but not more than 19,06 mm</li> </ul> for use in the production of self-propelled lawn mowers with a seat of subheading 8433 11 51, and tractors of subheading 8701 91 90, whose main function is that of a lawn mower (1)
8501 20 00		1443120/2017	Universal AC/DC motor with <ul style="list-style-type: none"> <li>- a rated output of 1,2 kW,</li> <li>- a supply voltage of 230 V and</li> <li>- engine break</li> <li>- assembled to a reduction gear with drive components, which is contained in a plastic housing</li> </ul> for use as electric drive of lawnmower blades (1)
8504 40 82		1518661/2017	Rectifier: <ul style="list-style-type: none"> <li>- with an input AC voltage of 100-240 V at frequency of 50-60 Hz,</li> <li>- with two output DC voltages: 12 V (9-12 V) and 400 V (396-420 V),</li> <li>- output cables without connectors,</li> <li>- in a plastic enclosure with dimensions 110 x 60 x 38 mm</li> </ul> for use in the manufacture of products for personal care appliances with IPL (Intensive Pulse Light) (1)
8505 19 90		1514450/2017	Article of agglomerated ferrite intended to become a permanent magnet after magnetisation, <ul style="list-style-type: none"> <li>- in the form of a rectangular prism whether or not with two beveled edges at one end,</li> <li>- of a length of 27mm or more but not more than 32 mm (+/-0,15mm),</li> <li>- of a width of 8,5mm or more but not more than 9,5 mm (+0,05mm / -0,09mm),</li> <li>- of a thickness of 5,5mm or more but not more than 5,8 mm (+0/-0,2mm) and</li> <li>- of a weight of 6,1g or more but not more than 8,3 g</li> </ul>
8526 91 20 8527 29 00		1497716/2017	Integrated audio module (IAM) for use in the manufacture of motor vehicles of Chapter 8703 with a digital video output for connection to a digital touch screen monitor and a digital driver information module (DIM), capable of being interfaced to other Electronic Control Units (ECUs) in the vehicle, capable of communicating through LIN, FlexRay, MOST, Ethernet, LVDS and APIX communication buses, with: <ul style="list-style-type: none"> <li>- a HD radio tuner,</li> <li>- satellite navigation function dependent on Global Navigation Satellite System (GNSS) positioning signals,</li> <li>- a traffic Message Channel (TMC) tuner,</li> <li>- satellite navigation functionality with online traffic services,</li> <li>- phone services via USB or Bluetooth hands-free,</li> <li>- services via third party applications and online cloud services,</li> </ul> with or without: <ul style="list-style-type: none"> <li>- a CD and DVD drive</li> </ul>
8537 10 91		1445382/2017	Programmable memory controller for a voltage not exceeding 1000 V, for the operation of a combustion motor, comprising at least <ul style="list-style-type: none"> <li>- a printed circuit with active and passive components</li> <li>- an aluminium housing and</li> <li>- multiple connectors</li> </ul>
8537 10 98		1378843/2017	Control unit of the emergency call system containing the module: <ul style="list-style-type: none"> <li>- GSM,</li> <li>- whether or not GPS</li> </ul> for use in the manufacture of goods of Chapter 87 (1)
ex 8548 10 29	10	1500781/2017	Spent lithium-ion or nickel metal hydride electric accumulators
8708 40 20		1445582/2017	Automatic gearbox with a hydraulic torque converter, with at least eight gears, for

			engine torque of minimum 300 Nm and transverse installation for use in the manufacture of motor vehicles of Chapter 8703
8708 91 99		1323371/2017	Assembly for supplying compressed air, whether or not with resonator, comprising at least: <ul style="list-style-type: none"> <li>- one solid aluminium tube whether or not with mounting bracket,</li> <li>- one flexible rubber hose,</li> <li>- one metal clip</li> </ul> for use in the manufacture of goods of Chapter 87 (1)
8708 99 97		1296602/2017	Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for connecting the gearbox to the car body for use in the manufacture of goods of Chapter 87 (1)
8708 99 97		1565442/2017	Electroplated interior or exterior parts for motor vehicles, consisting of: <ul style="list-style-type: none"> <li>- copolymers of acrylonitrile, butadiene and styrene (ABS), whether or not mixed with polycarbonate,</li> <li>- a layer of copper, nickel or chromium, and</li> <li>- a coating</li> </ul>
8708 99 97		1323284/2017	Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for connecting the gearbox to the car body for use in the manufacture of goods of Chapter 87 (1)
8714 93 00		1388100/2017	Sprocket-wheel gear single or gears connecting from 1 to 12 gears, for use in the production of bicycles
8714 93 00		1451889/2017	Hubs, other than coaster-type hub (torpedo), excluding internal gear hub and a hub equipped with XD cassette freewheel system for 11 and 12 gear cassettes tightened on the free hub body, for use in the production of bicycles
8714 94 20		1388008/2017	Brakes, manually operated, mechanical or hydraulic, for use in the production of bicycles
8714 94 90		1381486/2017	Brake levers or brake levers integrated with derailleur shifter lever, mechanical or hydraulic, for use in the production of bicycles
8714 99 50		1388055/2017	External derailleurs, front or rear, manually operated, mechanical or electromechanical, for use in the production of bicycles
ex 2804 50 90	10	1287/2008	ROUND 2018 -01 15-3 DE Request for amendment  Tellurium (CAS RN 13494-80-9) of a purity by weight of 99.99 % or more, but not more than 99.999 % by weight, based on the specific metals [or metallic impurities] according to ICP Analysis  Tellurium of a purity by weight of 99,99 % or more, but not more than 99,999 % (CAS RN 13494-80-9)
ex 2811 22 00	70	3863286/2015	Amorphous silicon dioxide (CAS RN 60676-86-0), <ul style="list-style-type: none"> <li>- in the form of powder</li> <li>- of a purity by weight of 99,0 % or more</li> <li>- with a median grain size of 0,7 µm or more, but not more than 2,1 µm</li> <li>- where 70 % of the particles have a diameter of not more than 3 µm</li> </ul> AT 10.03.2017  Amorphous silicon dioxide (CAS RN 60676-86-0), <ul style="list-style-type: none"> <li>- in the form of powder</li> <li>- of a purity by weight of 99,7 % or more</li> <li>- with a median grain size of 0,7 µm or more, but not more than 2,1 µm</li> <li>- where 70 % of the particles have a diameter of not more than 3 µm</li> </ul>
ex 2909 60 00	40	329376/2011	15-03 NL Request  1,3-di(2-tert-butylperoxyisopropyl) benzene (CAS RN 2212-81-9), 1,4-Di(2-tert-butylperoxyisopropyl)benzene (CAS RN 2781-00-2) or a mixture of these isomers.  1,4-Di(2-tert-butylperoxyisopropyl)benzene (CAS RN 2781-00-2) or mixture of isomers 1,4-Di(2-tert-butylperoxyisopropyl)benzene and 1,3-di(2-tert-butylperoxyisopropyl)benzene (CAS RN 25155-25-3)
ex 2916 13 00	10	1105/2009 3155/2/2000 PROLONG 2015 PROLONG 2016	Hydrozine methacrylate/ [Zinc Monomethacrylate] powder (CAS No. 63451-47-8) [whether or not containing not more than 17 % by weight of manufacturing impurities] IE 06.03. 2017  Hydroxyzinc methacrylate powder (CAS RN 63451-47-8)
ex 2917 39 95	70	1242209/2015	1,2,4-Benzenetricarboxylic acid, 1,2,4-trioctyl ester (CAS RN 89-04-3) with a purity by weight of more than 96 %
ex 2921 44 00	20	1884/1/2002	Diphenylamine (CAS RN 122-39-4)
ex 2928 00 90	60	1306/1/2003	Adipohydrazide (CAS RN 1071-93-8)
ex 2932 99 00	80	905/06	1,3:2,4-bis-O-(4-Methylbenzylidene)-D-glucitol (CAS RN 81541-12-0)

ex 2933 49 90	25	1345853/2016	ROUND 2018-01 21-02 UK Request for amendment  Cloquintocet-mexyl (ISO) (CAS RN 99607-70-2)  Cloquintocet-mexyl (ISO) (CAS RN 99607-70-2) for use in the formulation of herbicides (1)
ex 2934 99 90	35	1687/6/1996	ROUND 2018-01 15-03 DE Request for amendment Dimethenamide-P (CAS RN 163515-14-8)  Dimethenamide (ISO) (CAS RN 87674-68-8)
ex 2934 99 90	38	3957010/2015	Clomazone (ISO) (CAS RN 81777-89-1) with a purity by weight of 96 % or more
ex 3204 11 00	30	605497/2010 PROLONG 2016	TR description proposal: Preparation of dispersion dyes, containing: - C.I. Disperse Orange 61 or Orange 288, - C.I. Disperse Blue 291:1, - C.I. Disperse Violet 93:1, - Whether or not containing C.I. Disperse Red 54  Preparation of dispersion dyes, containing: - C.I. Disperse Orange 61, - C.I. Disperse Blue 291:1, - C.I. Disperse Violet 93:1, - C.I. Disperse Red 54
ex 3204 17 00	12	647239/2014	Colourant C.I. Pigment Orange 64 (CAS RN 72102-84-2) and preparations based thereon with a colourant C.I. colourant orange 64 content of 90 % or more by weight
ex 3204 17 00	60	246360/2011	Colourant C.I. Pigment Red 53:1 (CAS RN 5160-02-1) and preparations based thereon with a colourant C.I. Pigment Red 53:1 content of 50 % or more by weight
ex 3208 90 19	35	450754/2013	ROUND 2018-01 14-03 NL Request for amendment  Silicones containing 50 % by weight or more of xylene and not more than 25 % by weight of silica, of a kind used for the manufacture of long term surgical implants  Silicones containing 50 % by weight or more of xylene of a kind used for the manufacture of long term surgical implants
ex 3811 29 00	55	826457/2014	Additives consisting of reaction products of diphenylamine and branched nonenes with: - by weight more than 28 %, but not more than 35 % of 4-mono-nonyldiphenylamine, and - by weight more than 50 % but not more than 65 % of 4,4'-dino-nonyldiphenylamine, - by weight a total percentage of 2, 4-dino-nonyldiphenylamine and 2, 4'-dino-nonyldiphenylamine of not more than 5 %, used for the manufacture of lubricating oils (1)
ex 3824 99 92	22	3675407/2015	DE 01.03.2017 Request for amendment  Aqueous solution containing by weight - 10 % or more but not more than 42 % of 2-(3-chloro-5-(trifluoromethyl)pyridin-2-yl)ethanamine (CAS RN 658066-44-5), - 10 % or more but not more than 25 % of sulphuric acid (CAS RN 7664-93-9) and - 0,5 % or more but not more than 2,9 % of methanol (CAS RN 67-56-1)  Aqueous solution containing by weight - 38 % or more but not more than 42 % of 2-(3-chloro-5-(trifluoromethyl)pyridin-2-yl)ethanamine (CAS RN 658066-44-5), - 21 % or more but not more than 25 % of sulphuric acid (CAS RN 7664-93-9) and - 1 % or more but not more than 2,9 % of methanol (CAS RN 67-56-1)
ex 3824 99 92 ex 3824 99 92	35 39	906/06	UK 15.03.2017 Preparations of 1,3:2,4-bis-O-benzylidene-D-glucitol  Preparation containing not less than 47 % by weight of 1,3:2,4-bis-O-benzylidene-

			<i>D</i> -glucitol
ex 3824 99 92	44	167394/2010 PROLONG 2016	15-3 BE Request for amendment  Preparation containing by weight: - 85 % or more but not more than 99 % of polyethylene glycol ether of butyl 2-cyano 3-(4-hydroxy-3-methoxyphenyl) acrylate, and - 1 % or more but not more than 15 % of polyoxyethylene (20) sorbitan trioleate.  Preparation containing by weight: - 85 % or more but not more than 95 % of $\alpha$ -4-(2-cyano-2-butoxycarbonyl)vinyl-2-methoxy-phenyl- $\omega$ -hydroxyhexa(oxyethylene), and - 5 % or more but not more than 15 % of polyoxyethylene (20) sorbitan monopalmitate
ex 3824 99 93	77	366234/2013	IE 15 -03 Request for amendment  Powder Mixture containing by weight: - 85 % or more of Zinc Diacrylate (CAS RN 14643-87-9) - And not more than 5 % of 2,6-di-tert-butyl-alpha-dimethylamino-p-cresol (CAS RN 88-27-7) - [and containing between 0 % and 10 % of the reaction by-product Zinc Stearate (CAS RN 557-05-1)]  Powder mixture containing by weight: - 85 % or more of zinc diacrylate (CAS RN 14643-87-9) - and not more than 5 % of 2,6-di-tert-butyl-alpha-dimethylamino-p-cresol (CAS RN 88-27-7)
ex 3905 91 00	30	1048299/2012	01-03 DE Request for amendment  Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 38 % of the monomer unit ethylene  Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing not more than 32 % by weight of ethylene
ex 3919 90 80	60	170268/2010 PROLONG 2016	ROUND 2018-01 14-03 NL Request for amendment  Reflecting film consisting of: - whether or not a poly(vinyl chloride) layer - a polyurethane layer, - a glass microspheres layer, - a layer whether or not incorporating security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use - a metallised aluminium layer, and - an adhesive, covered on one or both sides with a release liner  Reflecting film containing: - a poly(vinyl chloride) layer, - a polyurethane layer, - a glass microspheres layer, - a layer whether or not incorporating a security and/or official mark which changes appearance with angle of view, - a metallised aluminium layer, and - an adhesive, covered on one side with a release liner
ex 3926 90 97	20	753915/2014	Housings, housing parts, drums, setting wheels, frames, covers and other parts of acrylonitrile-butadiene-styrene or polycarbonate, of a kind used for the manufacture of remote controls AT 10.03.2017  Housings, housing parts, drums, setting wheels, frames, covers and other parts of acrylonitrile-butadiene-styrene of a kind used for the manufacture of remote controls
ex 7409 19 00 ex 7410 21 00	10 70	362769/2013	Plates, rolls or sheets: - with at least one layer of woven glass fibre, impregnated with a fire- retardant artificial or synthetic resin with a glass transition temperature (Tg) of more than 130 °C as measured according to IPC-TM-650, method 2.4.25, - coated on one or both sides with a copper film with a thickness of not more than 3,2 mm, for use in the manufacture of circuit boards (1)



ex 8108 20 00	50	3962132/2015	<p>ROUND 2018-01 15-3 UK Request for amendment</p> <p>Titanium alloy ingot, • with a height of 17.8 cm or more, a length of 180 cm or more, a width of 48.3 cm or more • a weight of 680 kg or more, containing alloy elements by weight of: • 3 % or more but not more than 7 % of aluminium • 1 % or more but not more than 5 % of tin • 3 % or more but not more than 5 % of zirconium • 4 % or more but not more than 8 % of molybdenum</p> <p>Titanium alloy ingot, - with a height of 17,8 cm or more, a length of 180 cm or more and a width of 48,3 cm or more, - a weight of 680 kg or more, containing alloy elements by weight of: - 3 % or more but not more than 7 % of aluminium - 1 % or more but not more than 5 % of tin - 3 % or more but not more than 5 % of zinc - 4 % or more but not more than 8 % of molybdenum</p>
ex 8108 90 50	10	938/1/2004	<p>ROUND 2018-01 8-3 SI Request for amendment</p> <p>Requested amended description:</p> <p>Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 4,0 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 10 and 8708 92</p> <p>Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 3,1 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 10 (1)</p>
ex 8108 90 50	15	783675/2014	<p>Alloy of titanium, copper, tin, silicon, and niobium containing by weight: - 0,8 % or more but not more than 1,2 % of copper, - 0,9 % or more but not more than 1,15 % of tin, - 0,25 % or more but not more than 0,45 % of silicon and - 0,2 % or more but not more than 0,35 % of niobium, in sheets, plates, strips or foil</p>
ex 8108 90 50	25	982750/2011	Strip of titanium alloy
ex 8108 90 50	30	844/2006	<p>Alloy of titanium and silicon, containing by weight 0,15 % or more but not more than 0,60 % of silicon, in sheets or rolls, for use in the manufacture of: - exhaust systems for internal combustion engines or - tubes and pipes of subheading 8108 90 60 (1)</p>
ex 8108 90 50	50	1174/2007	Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium
ex 8108 90 50	60	1132/2008	<p>Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight: - 0,4 % or more but not more than 0,6 % of aluminium, - 0,35 % or more but not more than 0,55 % of silicon and - 0,1 % or more but not more than 0,3 % of niobium</p>
ex 8108 90 50	75	979263/2011	<p>Plates, sheets, strips and foil of titanium alloy, containing by weight: - 0,3 % or more but not more than 0,7 % of aluminium and - 0,25 % or more but not more than 0,6 % of silicon</p>
ex 8409 91 00	20	1302002/2016	<p>ROUND 2018-01</p> <p>SK Request for amendment</p> <p>Fuel injector with solenoid valve for optimized atomization in the combustion chamber for use in the manufacture of spark-ignition internal combustion piston engines of motor vehicles</p> <p>Fuel injector with solenoid valve for optimized atomization in the engine combustion chamber for spark-ignition internal combustion piston engines for use in the manufacture of motor vehicles of Chapter 87</p>

			(1)
ex 8409 91 00 ex 8409 99 00	30 50	371591/2013	DE 15.03.2017 Exhaust manifold with turbine housing of turbochargers with: <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C,</li> <li>- a hole to insert a turbine wheel, whereby a hole has a [maximum] diameter of 28 mm or more, but not more than 130 mm</li> </ul> Exhaust manifold with spiral-shaped gas turbine turbocharger component with: <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm</li> </ul>
ex 8411 99 00	60	311397/2012	ROUND 2018-01  DE Request for amendment  Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: <ul style="list-style-type: none"> <li>- of a precision-cast nickel based alloy complying with the following materials G- NiCr13Al6MoNb or G- NiCr12Al6MoNb or G- NiCo10W10Cr9AlTi or AMS AISI:686,</li> <li>- with a heat-resistance of not more than 1 100 °C,</li> <li>- with a diameter of 28 mm or more, but not more than 130 mm,</li> <li>- with a height of 20 mm or more, but not more than 85 mm</li> </ul> FR Request for amendment  Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: <ul style="list-style-type: none"> <li>- of a precision-cast nickel based alloy complying with standard DIN G- NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686,</li> <li>- with a heat-resistance of not more than 1 100 °C,</li> <li>- with a diameter of 30 mm or more, but not more than 180 mm,</li> <li>- with a height of 20 mm or more, but not more than 150 mm"</li> </ul> Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: <ul style="list-style-type: none"> <li>- of a precision-cast nickel based alloy complying with standard DIN G- NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686,</li> <li>- with a heat-resistance of not more than 1 100 °C;</li> <li>- with a diameter of 30 mm or more, but not more than 100 mm;</li> <li>- with a height of 20 mm or more, but not more than 70 mm</li> </ul>
ex 8411 99 00	65	371591/2013	DE 15.03.2017: Request for amendment  Turbine housing of turbochargers with: <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C,</li> <li>- a hole to insert a turbine wheel, whereby a hole has a [maximum] diameter of 28 mm or more, but not more than 130 mm</li> </ul> Spiral-shaped gas turbine turbocharger component: <ul style="list-style-type: none"> <li>- with a heat-resistance of not more than 1 050 °C, and</li> <li>- with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm</li> </ul>
ex 8414 59 25	30	1236/2008	Axial fan: <ul style="list-style-type: none"> <li>- with an electric motor,</li> <li>- of an output of not more than 125 W</li> </ul> for use in the manufacture of computers (1)
ex 8415 90 00	50	3869484/2015	ROUND 2018-01 08-03 PL Request for description amendment  Aluminium arc-welded removable receiver dryer with polyamide and ceramic elements with: <ul style="list-style-type: none"> <li>- a length of 143 mm or more but not more than 292 mm,</li> <li>- a diameter of 31 mm or more but not more than 99 mm,</li> <li>- a spangle length of not more than 0,2 mm and a thickness of not more than 0,06 mm,</li> <li>- a solid particle diameter of not more than 0,06 mm</li> </ul> of a kind used in car air-conditioning systems

			Aluminium arc-welded removable receiver dryer with polyamide and ceramic elements with: <ul style="list-style-type: none"> <li>- a length of 291 mm (+/- 1 mm),</li> <li>- a diameter of 32 mm (+/- 1 mm),</li> <li>- a spangle length of not more than 0,2 mm and a thickness of not more than 0,06 mm,</li> <li>- a solid particle diameter of not more than 0,06 mm</li> </ul> of a kind used in car air-conditioning systems
8481 90 00		5457613/2016	Rollover from the previous Round 7.11.16 LT proposal:  Exhaust gas recirculation (EGR) valve housing cast of aluminium alloy complying with standard EN-1706-AC-44300D or EN-1706-AC-47100D.  Exhaust gas recirculation (EGR) valve housing made of aluminium alloy complying with standard EN-1706-AC-44300D or EN-1706-AC-47100D
8481 90 00		5457584/2016	Exhaust gas recirculation (EGR) valve tube made of aluminium alloy complying with standard EN-1706-AC-47100D
ex 8482 10 10 ex 8482 10 90	30 20	847423/2014	DE 09.03.2017: Amending Request Ball bearings: <ul style="list-style-type: none"> <li>- with an internal diameter of 3 mm or more,</li> <li>- with an external diameter of not more than 100 mm,</li> <li>- with a width of not more than 40 mm,</li> <li>- whether or not equipped with a duster,</li> </ul> for use in the manufacture of belt drive steering systems of motor, electric power steering systems or steering gears or assy ball screw for steering gears  Ball bearings: <ul style="list-style-type: none"> <li>- with an internal diameter of 3 mm or more,</li> <li>- with an external diameter of not more than 100 mm,</li> <li>- with a width of not more than 40 mm,</li> <li>- whether or not equipped with a duster,</li> </ul> for use in the manufacture of belt drive steering systems of motor, electric power steering systems or steering gears (1)
8483 30 32 ex 8483 30 38	40	311427/2012	13.03.2017 - DE: Request for amendment Bearing housing of a kind used in turbochargers: <ul style="list-style-type: none"> <li>- of precision-cast grey cast iron complying with standard DIN EN 1561,</li> <li>- with oil chambers,</li> <li>- without bearings,</li> <li>- with a diameter of 50 mm or more, but not more than 250 mm,</li> <li>- with a height of 40 mm or more, but not more than 150 mm,</li> <li>- whether or not with water chambers and connectors</li> </ul> Cylindrical bearing housing: <ul style="list-style-type: none"> <li>- of precision-cast grey cast iron complying with standard DIN EN 1561,</li> <li>- with oil chambers,</li> <li>- without bearings,</li> <li>- with a diameter of 50 mm or more, but not more than 250 mm,</li> <li>- with a height of 40 mm or more, but not more than 150 mm,</li> <li>- whether or not with water chambers and connectors</li> </ul>
ex 8501 31 00	33	1268149/2016	Brushless DC motor assembly comprised of a motor and transmission, with: <ul style="list-style-type: none"> <li>- electronic control operating by Hall Effect position sensors</li> <li>- voltage input 9V or more but not more than 16V,</li> <li>- external diameter of the motor 70 mm or more but not more than 80 mm,</li> <li>- output motor power 350 W or more but not more than 550W</li> <li>- maximum output torque 50 Nm or more but not more than 52 Nm,</li> <li>- maximum output rotation speed 280 rpm or more but not more than 300 rpm</li> <li>- coaxial male spline outputs of outer diameter 20 mm (+/- 1 mm), 17 teeth and minimum length of teeth 25 mm (+/- 1 mm),</li> <li>- with distance between root of splines 119 mm (+/- 1 mm)</li> </ul> for use in the manufacture of all-terrain or utility task vehicles PL 08.03.2017  Brushless DC motor assembly comprised of a motor and transmission, with: <ul style="list-style-type: none"> <li>- an electronic control operating by Hall Effect position sensors,</li> <li>- a voltage input 9 V or more but not more than 16 V,</li> <li>- an external diameter of 70 mm or more but not more than 80 mm,</li> <li>- an output motor power 450 W or more but not more than 500 W,</li> <li>- a maximum output torque 50 Nm or more but not more than 52 Nm,</li> <li>- a maximum output rotation speed 280 rpm or more but not more than 300 rpm,</li> <li>- a coaxial male spline outputs with an outer diameter of 20 mm (±1 mm), 17</li> </ul>

			teeth and a minimum length of the teeth of 25 mm ( $\pm$ 1 mm), and - a distance between root of splines of 119 mm ( $\pm$ 1 mm) for use in the manufacture of all-terrain or utility task vehicles  (1)
ex 8501 31 00 ex 8501 32 00	35 70	3812069/2015	Automotive-ready, brushless and permanently excited direct current motor with: - a specified speed of not more than 4 000 rpm, - a minimum output of 400 W, but not more than 1,3 kW (at 12V), - a flange diameter of 90 mm or more, but not more than 150 mm, - a maximum length of 190 mm, measured from the beginning of the shaft to the outer ending, - a housing length of not more than 150 mm, measured from the flange to the outer ending, - a two-piece (basic housing including electric components and flange with minimum 2 and maximum 6 bore holes) aluminium diecast housing with a sealing compound (groove with an O-ring and grease), - a stator with single T-tooth design and single coil windings in 12/8 topology and - surface magnets
ex 8504 40 90	25	778/1/1993	Direct current to direct current converter - without housing or - with housing with connection pins, connection studs, screw connectors, unprotected line connections, connection elements which allow the mounting to a printed circuit board by soldering or any other technology, or other wiring connections requiring further processing
ex 8511 30 00	50	1302174/2016	ROUND 2018-01 6-3 SK Request for amendment Ignition coil: - with a length of 50 mm or more, but not more than 200 mm, - with an operating temperature of $-40$ °C or more, but not more than 140 °C, and - with a voltage of 9 V or more, but not more than 16 V, - with or without connection cable, for use in the manufacture of engines of motor vehicles. (2)"  Ignition coil: - with a length of 50 mm or more, but not more than 200 mm, - with an operating temperature of $-40$ °C or more, but not more than 140 °C, and - with a voltage of 9 V or more, but not more than 16 V, - with or without connection cable, for use in the manufacture of motor vehicles of Chapter 87  (1)
ex 8536 90 95	30	3863451/2015	Rivet contacts - of copper - plated with silver nickel alloy AgNi10 or with silver containing by weight 11,2 % ( $\pm$ 1,0 %) of tin oxide and of indium oxide taken together - whether or not gilded - with a thickness of the plating of 0,3 mm ( $-0/+0,015$ mm) AT 10.03.2017  Rivet contacts - of copper - plated with silver nickel alloy AgNi10 or with silver containing by weight 11.2 % ( $\pm$ 1.0 %) of tin oxide and of indium oxide taken together - with a thickness of the plating of 0,3 mm ( $-0/+0,015$ mm)
ex 8537 10 98	92	1790/1/1997	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors
ex 8544 20 00	20	1233197/2015	Antenna connecting cable, containing: - a coaxial cable, - two or more connectors, - 3 or more plastic clips for attachment to the dashboard of kind used in the manufacture of goods of Chapter 87 SK 06.03.2017  Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing: - a coaxial cable, - two or more connectors, - 3 or more plastic clips for attachment to the dashboard of kind used in the manufacture of goods of Chapter 87
ex 8544 30 00	35	1268178/2016	Wire harness:- with an operation voltage of 12V,- wrapped in tape or covered in

			<p>plastic convoluted tubing, - with 16 or more strand, with all terminals to be tin plated or equipped with connectors, for use in the manufacture of all-terrain or utility task vehicles PL 08.03.2017</p> <p>Wire harness:</p> <ul style="list-style-type: none"> <li>- with an operation voltage of 12 V,</li> <li>- wrapped in tape and covered in plastic convoluted tubing,</li> <li>- with 16 or more strand, with all terminals to be tin plated or equipped with connectors,</li> </ul> <p>for use in the manufacture of all-terrain or utility task vehicles</p>
ex 8544 30 00 ex 8544 42 90	80 60	3883526/2015	<p>SK 06.03.2017</p> <p>Extension two-core cable with two connectors, containing at least:</p> <ul style="list-style-type: none"> <li>- a rubber grommet,</li> <li>- a metal attachment bracket</li> </ul> <p>of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87</p> <p>Extension two-core cable with two connectors, containing at least:</p> <ul style="list-style-type: none"> <li>- a rubber grommet,</li> <li>- a plastic conduit,</li> <li>- a metal attachment bracket</li> </ul> <p>of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87</p>
ex 8708 40 20 ex 8708 40 50	10 20	1272648/2016	<p>Gear box assembly with one or two inputs and at least three outputs in cast aluminum housing with overall dimensions (excluding the shafts) of not more than 455 mm (width) x 462 mm (height), 680 mm length, equipped with at least:</p> <ul style="list-style-type: none"> <li>- one exterior-splined output shaft</li> <li>- a rotary switch to indicate gear position</li> <li>- the potential for a differential</li> </ul> <p>for use in the manufacture of all-terrain or utility task vehicles PL 08.03.2017</p> <p>Gear box assembly with one or two inputs and three outputs in cast aluminum housing with overall dimensions of not more than 445 mm (width) x 462 mm (height), 680 mm length, equipped with:</p> <ul style="list-style-type: none"> <li>- one exterior-splined output shaft,</li> <li>- two interior-splined, coaxial output shafts,</li> <li>- a rotary switch to indicate gear position, and</li> <li>- the potential for a differential to be incorporated between the 2 coaxial output shafts,</li> </ul> <p>for use in the manufacture of all-terrain vehicles or utility task vehicles (1)</p>
ex 8708 50 20 ex 8708 50 99 ex 8708 99 10 ex 8708 99 97	30 20 20 70	1272733/2016	<p>Single input, dual output gearcase (transmission) in cast aluminum housing, with overall dimensions of 273 mm (width) x 131 mm (height) x 187 mm (length). Comprising at least:</p> <ul style="list-style-type: none"> <li>- two electro-magnetic one direction clutches in one cage, working in opposite sides,</li> <li>- an input shaft with outer diameter of 24 mm (+/- 1 mm), ended with 22 teeth spline,</li> <li>- a coaxial output bushing with inner diameter of 22 mm (+/- 1 mm), ended with 22 teeth spline</li> </ul> <p>for use in the manufacture of all-terrain or utility task vehicles PL 08.03.2017</p> <p>Single input, dual output gearcase (transmission) in a cast aluminum housing, with overall dimensions of 273 mm (width) x 131 mm (height) x 187 mm (length), comprising at least:</p> <ul style="list-style-type: none"> <li>- two electro-magnetic one direction clutches, working in opposite sides,</li> <li>- an input shaft with an outer diameter of 24 mm (+/- 1 mm), ended with 22 teeth spline, and</li> <li>- a coaxial output bushing with an inner diameter of 22 mm (+/- 1 mm), ended with 22 teeth spline</li> </ul> <p>for use in the manufacture of all-terrain vehicles or utility task vehicles (1)</p>
ex 8708 93 10 ex 8708 93 90	20 20	1268238/2016	<p>Mechanically operated centrifugal clutch for use with an elastomeric belt in a dry environment in a continuously variable transmission (CVT), equipped with:</p> <ul style="list-style-type: none"> <li>- elements that activate the clutch at given rotation and generate (in this way) centrifugal force</li> <li>- shaft ended with 5 or more but not more than 6 degree taper</li> <li>- 3 weights</li> <li>- 1 compression spring</li> </ul> <p>for use in the manufacture of all-terrain or utility task vehicles PL 03.08.2017</p>

			<p>Mechanically operated centrifugal clutch for use with an elastomeric belt in a dry environment in a continuously variable transmission (CVT), equipped with:</p> <ul style="list-style-type: none"> <li>- elements that activate the clutch at given rotation and generate (in this way) centrifugal force,</li> <li>- shaft ended with five degree taper,</li> <li>- three weights, and</li> <li>- one compression spring</li> </ul> <p>for use in the manufacture of all-terrain or utility task vehicles (1)</p>
ex 9001 50 41 ex 9001 50 49	30 30	825118/2014	<p>Organic uncut corrective eyeglass lens, finished on both sides, suitable to undergo a coating, coloring, edging, mounting or any other substantial process FR 15.03.2017</p> <p>Round organic uncut corrective eyeglass lens, finished on both sides, suitable to undergo a coating, coloring, edging, mounting or any other substantial process DE 14.03.2017</p> <p>Round organic uncut corrective eyeglass lens blanks, finished on both sides:</p> <ul style="list-style-type: none"> <li>- of a diameter of 4,9 cm or more but not more than 8,2 cm,</li> <li>- of a height of 0,5 cm or more but not more than 1,8 cm, measured when the lens is laid on a flat surface from the horizontal plane to the lens front surface centre</li> </ul> <p>of a kind used to be processed in order to be adapted to a pair of glasses (1)</p>
ex 9001 90 00	60	1159/2008	<p>DE 02.03.2017</p> <p>Reflector or diffuser sheets, in rolls,</p> <ul style="list-style-type: none"> <li>- for protection against ultraviolet or infra-red heat radiation, to be affixed to windows or</li> <li>- for equal transmission and distribution of light, intended for LCD modules</li> </ul> <p>Reflector or diffuser sheets in rolls</p>
ex 9002 11 00	80	3076474/2014	<p>DE 15.03.2017(request for amendment)</p> <p>Lens assembly with:</p> <ul style="list-style-type: none"> <li>- a horizontal field of view range of 58,5 deg or more, but not more than 200 deg,</li> <li>- a focal length of 1,16 mm or more, but not more than 3,88 mm,</li> <li>- a relative aperture of F/2.0 or more but not more than 2.6,</li> <li>- a diameter of 5 mm or more but not more than 18,5 mm,</li> </ul> <p>or use in the manufacture of CMOS automotive cameras</p> <p>Lens assembly with:</p> <ul style="list-style-type: none"> <li>- a field of view range of 58,5 deg or more, but not more than 194 deg,</li> <li>- a focal length of 1,16 mm or more, but not more than 3,88 mm,</li> <li>- a relative aperture of F/2.0 or more but not more than 2.6,</li> <li>- a diameter of 17 mm or more but not more than 18,5 mm,</li> </ul> <p>for use in the manufacture of CMOS automotive cameras (1)</p>

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)

**EK – 3**

**EKONOMİ BAKANLIĞI**  
**İthalat Genel Müdürlüğüne**

Avrupa Birliği ile Türkiye arasında ihdas edilen Gümrük Birliği çerçevesinde, .../.../... Dönemi itibariyle gümrük vergilerinin müştereken askıya alınması ve/veya otonom tarife kontenjani açılması talep edilen ve/veya hâlihazırda İthalat Rejimi Kararı Eki V sayılı listede yer alan ürünlere ilişkin Bakanlığınız resmi internet sitesinde yayımlanan liste kapsamındaki aşağıda belirtilen ürün(ler)de üretimimiz olması gerekçesiyle, söz konusu ürünlerin Askıya Alma Sistemi kapsamına alınmasına itiraz etmekteyiz.

Gereğinin yapılmasını saygılarımla arz ederim.

İtiraz Konusu Ürünün Dosya Numarası	
İtiraz Konusu Ürünün Tarife Pozisyonu	
Talep Konusu Ürünün Tanımı	

Firma Yetkilisi  
Adı Soyadı, Unvan  
İmza ve Kaşe

**Başvuruya Eklenacak Belgeler:**

- 1) İtiraz Formu (EK – 6)
- 2) Talep konusu ürünün tedarikine ilişkin talep sahibi firma ile üretici (itiraz eden) firma arasındaki görüşmelere dair bilgi ve belgeler
- 3) Geçerli Kapasite Raporu
- 4) Ürüne ilişkin teknik bilgi ve belgeler

## EK -6

### ASKIYA ALMAYA / OTONOM TARİFE KONTENJANI AÇILMASINA İLİŞKİN İTİRAZ FORMU (Talebe uygun olan seçilir)

#### Kısım I

1. Talep No:

2. Tarife Pozisyonu:

3. Talep konusu ürüne ilişkin uygun ürün tanımı:

4. Sıra No:

- Ürün(ler) AB ve Türkiye’de hâlihazırda üretilip piyasa arz ediliyor.
- Eşdeğer veya ikame ürün(ler) hâlihazırda üretilip piyasa arz ediliyor.

Açıklayıcı bilgi (talep konusu ürünü hangi şekilde ikame edeceği)

Eşdeğer/ikame ürüne ilişkin teknik bilgi/belgeler

- Diğer

5. İtirazın içeriği:

Tarife kontenjanına çevrilmesi:  
Önerilen tarife kontenjanı miktarı:

Kısmi askıya almaya çevrilmesi:  
Önerilen gümrük vergisi oranı:

Diğer:

6. İtiraz konusu ürünün aynısının, eşdeğerinin veya ikamesinin AB veya Türkiye’de yerleşik üreticisi:

Firma Adı:

Firma Yetkilisi:

Adres:

Telefon/Faks:

E-posta:

Ürünün ticari adı:



**ASKIYA ALMAYA / OTONOM TARİFE KONTENJANI AÇILMASINA İLİŞKİN  
İTİRAZ FORMU (Talebe uygun olan seçilir)**

**Kısım II**

7. Üretim kapasitesi (Piyasa arz edilmeye hazır, sözleşmeye bağlanmamış kapasite):

Mevcut:

Gelecek altı ay içerisinde:

## Vedat Çağlar

**Kimden:** İthalat Genel Müdürlüğü Sanayi 1 Dairesi <sanayi1@ekonomi.gov.tr>  
**Gönderme Tarihi:** 26 Nisan 2017 Çarşamba 15:09  
**Kime:** İthalat Genel Müdürlüğü Sanayi 1 Dairesi  
**Bilgi:** Cavit ÖZDEM; Okan ÖZTÜRK; Hasan ÖNER  
**Konu:** Sanayi Ürünlerinde Gümrük Vergilerinin Askıya Alınması Uygulaması  
**Ekler:** Form 2.docx; EK-3.docx; EK-6.docx; Ocak 2018'den Sonra Gümrük Vergisi İndirimi Talep Edilen Eşya.docx



### T.C. Ekonomi Bakanlığı İthalat Genel Müdürlüğü Sanayi I ve Sanayi II Daire Başkanlıkları

Sayın yetkili,

Bildiği üzere, Ülkemiz ile AB arasında ihdas olunan 1/95 sayılı Ortaklık Konseyi Kararı'nın 13 üncü Maddesi uyarınca sanayi ürünlerinde gümrük vergileri karşılıklı olarak sıfırlanmış olup, üçüncü ülkelere ise Ortak Gümrük Tarifesi uygulanmaktadır.

Diğer taraftan, ucuz hammadde temin etmek suretiyle sanayicimizin rekabet gücünü artırmak, modernize olmalarını sağlamak ve tüketici fiyatlarını düşürmek amacıyla, üçüncü ülkelerden gümrük vergisi ile ithal edilen, Ülkemiz ile AB'ye üye ülkelerde yerli üretimi olmayan Gümrük Birliği kapsamındaki sanayi ürünlerine ilişkin her yıl 1 Ocak ve 1 Temmuz tarihlerinde yürürlüğe girecek şekilde yapılan askıya alma, üretim tüketimi karşılamayan ürünlerde ise kota başvuruları, ülkemiz temsilcilerinin de yer aldığı Avrupa Komisyonu Gümrük Kodu Komitesi Ekonomik Tarife Sorunları Grubu (ETSG) tarafından müzakere edilerek karara bağlanmaktadır.

Bahsi geçen müzakereler sonucu gümrük vergisinin askıya alınması ve bu suretle gümrük vergisi oranının düşürülmesi veya sıfırlanması kararlaştırılan ürünler Toplulukla eş zamanlı olarak İthalat Rejimi Kararı Eki V Sayılı Listeye yansıtılmakta, ulusal tarife kontenjanları ise Bakanlar Kurulu Kararı ve kotanın dağıtımına ilişkin yayımlanan Tebliğler çerçevesinde dağıtılmaktadır.

Bu kapsamda, 1/1/2018 dönemine yönelik olarak askıya alma ve tarife kontenjanına ilişkin talepler alınmış olup, söz konusu talepler ekte yer almaktadır. Listede GTP ve tanımları yer alan eşyadan herhangi birini üretimlerinde hammadde olarak kullanan bu eşyada vergi indirimini desteklemek isteyen firmaların bir dilekçe ile, ülkemizde üretimi olduğu gerekçesiyle gümrük vergisinin düşürülmesine itiraz etmek isteyen firmaların ise ekte yer alan formlarla birlikte müracaatlarını **en geç 9 Haziran 2017 Cuma gününe kadar** Bakanlığımız genel evrakına girecek şekilde iletmeleri gerekmektedir. Bu çerçevede, üye firmalarınızın ivedilikle konuyla ilgili bilgilendirilmeleri önem arz etmektedir.

Bilgileri ve gereğini rica ederim.

Hasan ÖNER  
Bakan a.  
Daire Başkanı

Okan ÖZTÜRK  
Bakan a.  
Daire Başkanı

## İlgili Kişilerin İletişim Bilgileri :

### Kimyasallar, Maden-Metal ve Tekstil Hammaddeleri:

- |                         |            |                    |   |
|-------------------------|------------|--------------------|---|
| - Bekir Sıddık KIZMAZ   | Uzman      | T: 0 312 204 95 76 | E: <a href="mailto:kizmazb@ekonomi.gov.tr">kizmazb@ekonomi.gov.tr</a>                 |
| - Merve BAYATA          | Uzman Yrd. | T: 0 312 204 95 75 | E: <a href="mailto:mbayata@ekonomi.gov.tr">mbayata@ekonomi.gov.tr</a>                 |
| - M.Burak ATEŞTENYILMAZ | Uzman Yrd. | T: 0 312 204 95 79 | E: <a href="mailto:atestenyilmazmb@ekonomi.gov.tr">atestenyilmazmb@ekonomi.gov.tr</a> |

### Elektrik-Elektronik, Otomotiv ve Makine Ara Malları:

- |                         |            |                    |   |
|-------------------------|------------|--------------------|---|
| - Halil İbrahim KARATAŞ | Uzman Yrd. | T: 0 312 204 99 55 | E: <a href="mailto:karatash@ekonomi.gov.tr">karatash@ekonomi.gov.tr</a> |
| - Osman SERT            | Uzman Yrd  | T: 0 312 204 95 93 | E: <a href="mailto:osmans@ekonomi.gov.tr">osmans@ekonomi.gov.tr</a>     |
| - Ömer Furkan YÜKSEL    | Uzman Yrd. | T: 0 312 204 95 94 | E: <a href="mailto:yukselof@ekonomi.gov.tr">yukselof@ekonomi.gov.tr</a> |
| -Murat Özmen            | Uzman Yrd. | T: 0 312 204 99 38 | E: <a href="mailto:ozmenm@ekonomi.gov.tr">ozmenm@ekonomi.gov.tr</a>     |

İthalat Genel Müdürlüğü Söğütözü Mah. 2180 Cad. No 63 Kat:14 06530 Çankaya/Ankara  
Tel : 0 312 212 8752 Faks : 0 312 212 8765 0 312 204 8633 ( Ebys) Email : [sanayi1@ekonomi.gov.tr](mailto:sanayi1@ekonomi.gov.tr)

*Bu e-posta sadece yukarıda isimleri belirtilen kişiler arasında özel haberleşme amacını taşımaktadır. Size yanlışlıkla ulaşmışsa lütfen mesajı sisteminizden siliniz. T.C. Ekonomi Bakanlığı bu mesajın içeriği ile ilgili olarak hiçbir hukuksal sorumluluğu kabul etmez.*

*This e-mail communication is intended for the private use of the people named above. If you received this message in error, please immediately delete it from your system. Ministry of Economy does not accept legal responsibility for the contents of this message.*

Click [here](#) to report this email as spam.

**Form for:**

**OBJECTION TO A REQUEST FOR TARIFF SUSPENSION/TARIFF QUOTA**

(delete inappropriate measure)

(TURKEY )

**Part I**

Request No:

CN-Code:

Goods description:

Working No:

Goods are currently produced in the Union or Turkey and are available on the market.

Equivalent or substitute products are currently obtainable within the Union or Turkey.

Explanatory comments (differences, why and how it may replace the requested product):

Technical data sheets which prove the character and quality of the offered product have to be attached.

Other:

Suggested compromise (explanatory comments):

Transfer into a tariff quota:

Suggested quota volume:

Partial tariff suspension:

Suggested duty rate:

Other proposals:

Remarks:

**Company producing currently an identical, equivalent or substitute product**

**within the EU or Turkey**

Name of the company:

Person to contact:

Address:

Tel.:

Fax:

E-mail:

Product trade name:

**OBJECTION TO A REQUEST FOR TARIFF SUSPENSION/TARIFF QUOTA**

**(delete inappropriate measure)**

**(TURKEY )**

**Part II**

Production capacity (available for the market; e.g. not bound in house or by contracts):

Present:

Within the next six months:

\_\_\_\_\_